



Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon with TeraPlex® SD PET
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	6592 oz./y3 (244.44 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Warranties	Nexus Modular Commercial Adhesive for Modular Carpet & LVT Nexus FC Cushion Encore SD Nylon with TeraPlex SD PET Fiber
Optional Warranties	Commercial High Moisture Adhesive for Modular Carpet and LVT Advance Modular Backing

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	37.77%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Quarter Turn

Colorways



ARV44 Blue Moon

ARV56 Flint

ARV58 Ebony

ARV74 Sepia