



Product Specifications

|                     |  |
|---------------------|--|
| Construction        | Textured Loop  |
| Backing             | PremierBac® Plus   |
| Dye Method          | Solution Dyed  |
| Fiber Type          | Encore® SD Ultima® (with recycled content)   |
| Face Weight         | 22 oz./sy (746 grams/m2)   |
| Pile Density        | 8889 oz./y3 (329.61 kg/m3)   |
| Pattern Repeat      | 18.00" (w) x 24.00" (l) approx. (45.72cm x 60.96cm)                                  |
| Gauge               | 1/10 (3.94 rows/cm)  |
| Standard Width      | 12 ft 3.66 m   |
| Standard Adhesive   | Commercialon Premium Carpet Adhesive   |
| Standard Warranties | Commercialon Premium Broadloom Adhesive<br>PremierBac Plus<br>Encore SD Ultima Fiber |
| Optional Warranties | Endure Plus<br>TitanBac Plus<br>Nexus Cushion Modular Adhesive<br>Encore® 100 Fiber  |

Special Technologies


Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 50.7%                              |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |


Colorways



BTM24 Peche



BTM35 Bronze



BTM37 Vert




BTM45 Bleu




BTM49 Bleu Marine




BTM52 Argente




BTM54 Acier



BTM56 Gris



BTM58 Noir



BTM72 Beige



BTM78 Marron