



Installation Methods: Ashlar, 1/3 Drop, Herringbone

Product Specifications

| | |
|---------------------|---|
| Wear Layer | 20 mil |
| Thickness | 2.5mm |
| Finish / Coating | Enhanced UV Urethane w/ Ceramic Micro Bead |
| Pattern Repeat | Random Wood |
| Edge Treatment | None |
| Dimensions: | 6" x 48" |
| Standard Adhesive | Commercialon Premium Modular and LVT Adhesive |
| Backing Class | Commercial Grade |
| Commercial Traffic | Heavy Commercial |
| Standard Warranties | 15 Year LVT |
| Optional Warranties | Nexus Cushion Modular Adhesive |

Packaging

| | |
|---------------------------|--------------------------|
| Sq.ft. per piece / carton | 2 / 36 |
| Weight per piece / carton | 2.05 (lbs) / 36.97 (lbs) |
| Pieces per box | 18 |
| Boxes per pallet | 60 |


Special Technologies

| | |
|---------------------|-----|
| Added Antimicrobial | Yes |
|---------------------|-----|


Environmental Specifications & Tests

| | |
|------------------------------------|--|
| Indoor Air Quality | FloorScore® Certified |
| LEED v4 | Contributes to IAQ: Low Emitting Materials |
| End of Life | 100% Recyclable |
| Radiant Panel | Class 1 |
| ADA Compliance | Compliant For Accessible Routes |
| ASTM F2055 (Size and Tolerance) | Passes |
| ASTM F386 (Thickness) | Passes |
| ASTM F1914 (Residual Indentation) | Passes |
| ASTM F137 (Flexibility) | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resistance) | Passes |
| ASTM F1514 (Resistance to Heat) | Passes |
| ASTM F1515 (Resistance to Light) | Passes |
| ASTM E648 (Critical Radiant Flux) | Passes |
| ASTM E662 (Optical Smoke Density) | Passes |
| ASTM C1028 (Slip Resistance) | Passes |
| ASTM F970 (Static Load) | Passes |

Colorways




001 Manzanita



002 Chamis



003 Scrub Oak



004 Sumac



005 Sage Brush