



Product Specifications

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| Construction        | Textured Loop                                                                                                   |
| Backing             | PremierBac® Plus (A)                                                                                            |
| Dye Method          | Solution Dyed                                                                                                   |
| Fiber Type          | Encore® SD Ultima® (with recycled content)                                                                      |
| Face Weight         | 22 oz./sy (746 grams/m2)                                                                                        |
| Pile Density        | 7543 oz./y3 (279.70 kg/m3)                                                                                      |
| Pattern Repeat      | 6.00" (w) x .63" (l) approx. (15.24cm x 1.60cm)                                                                 |
| Gauge               | 1/10 (3.94 rows/cm)                                                                                             |
| Stitches Per Inch   | 12.7 stitches/in (5.00 stitches/cm)                                                                             |
| Standard Width      | 12 ft 3.66 m                                                                                                    |
| Standard Adhesive   | Commercial Premium Carpet Adhesive                                                                              |
| Standard Warranties | <b>Encore SD Ultima Fiber</b>                                                                                   |
| Optional Warranties | <b>Endure Plus</b><br><b>TitanBac Plus</b><br><b>Nexus Cushion Modular Adhesive</b><br><b>Encore® 100 Fiber</b> |


Special Technologies

|                        |          |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release   | Standard |
| Sentir® Odor-Blocker   | Optional |


Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 68.9%                              |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |


Colorways



CNT22 Standpoint




CNT47 Framework




CNT51 Ambience



CNT52 Relation



CNT54 Perspective



CNT57 Situation