



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

| | |
|---------------------|---|
| Construction | Patterned Loop |
| Backing | Nexus® Modular |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 15 oz./sy (509 grams/m2) |
| Pile Density | 6750 oz./y3 (250.29 kg/m3) |
| Pattern Repeat | N/A |
| Gauge | 1/12 (4.72 rows/cm) |
| Stitches Per Inch | 10 stitches/in (3.94 stitches/cm) |
| Standard Size | 24" x 24" approx. (60.96cm x 60.96cm) |
| Standard Adhesive | Commercialon Premium Modular and LVT Adhesive |
| Optional Adhesive | TileTabs |
| Standard Warranties | Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Nexus FC Cushion Encore SD Ultima Fiber |
| Optional Warranties | Advance Modular Backing Nexus Cushion Modular Adhesive Advance Modular Adhesive Tile Tabs Encore® 100 Fiber |


Special Technologies

| | |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |


Environmental Specifications & Tests

| | |
|------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 46.5% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways




CNL38 Emerald




CNL48 Sapphire




CNL52 Taupe




CNL54 Mineral



CNL56 Gunmetal



CNL58 Anthracite



CNL96 Violet