



Product Specifications

Construction	Tip-Sheared Scroll
Backing	PremierBac® Plus (A)
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	24 oz./sy (814 grams/m2)
Pattern Repeat	24.00" (w) x 48.00" (l) approx. (60.96cm x 121.92cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	11.5 stitches/in (4.53 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	67.6%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



CSS10 Tatami



CSS32 Tinsel




CSS45 Shadow



CSS47 Barkcloth




CSS48 Denim



CSS52 Grey Twill



CSS55 Stonewash



CSS58 Rattan



CSS72 Knitting Nee...



CSS76 Corduroy



CSS77 Tapestry Ta...



CSS86 Shuttle Bro...