



Product Specifications

Construction	Patterned Scroll
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	TeraPlex® SD PET
Face Weight	20 oz./sy (678 grams/m2)
Pile Density	8889 oz./y3 (329.61 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	<b>Commercialon Premium Broadloom Adhesive</b> <b>PremierBac Plus</b>
Optional Warranties	<b>Endure Plus</b> <b>TitanBac Plus</b>


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	26.15%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



CWK12 Driftwood




CWK15 Dapple Grey




CWK43 Lark




CWK46 Cobalt




CWK55 Lead



CWK56 Steel



CWK57 Slate



CWK58 Lampblack



CWK75 Acorn