



## Product Specifications

Construction	Textile Composite
Backing	Polyester Felt Cushion
Dye Method	Solution Dyed
Wear Layer	100% Solution Dyed Polyester
Pattern Repeat	N/A
Total Weight	4.5 oz - 5.2 oz/ square foot
Total Thickness	.205 inches
Dimensions:	24" x 24" modules
Standard Adhesive	Kinetex Adhesive
Packaging	18 modules per box (72 sq.ft)
Standard Warranties	<b>Kinetex Adhesive</b>
Optional Warranties	<b>Nexus Cushion Modular Adhesive</b>


## Special Technologies

## Environmental Specifications & Tests

Carbon Footprint:	Carbon Neutral
Recyclability:	100% Closed-loop Recyclable
NSF 140:	Platinum Certified
Total Recycled Content:	47%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

## Installation Methods: Quarter Turn


### Colorways



DAR24 Surge




DAR25 Dash




DAR34 Flash



DAR44 Whiz



DAR45 Sprint




DAR49 Hurry




DAR59 Zoom



DAR74 Bolt




DAR76 Gallop



DAR77 Fly



DAR79 Zip



DAR87 Spring



DAR99 Streak