



Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon with TeraPlex® SD PET
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	6592 oz./y3 (244.44 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Warranties	<b>Nexus Modular Commercial Adhesive for Modular Carpet &amp; LVT</b> <b>Nexus FC Cushion</b> <b>Encore SD Nylon with TeraPlex SD PET Fiber</b>
Optional Warranties	<b>Commercial High Moisture Adhesive for Modular Carpet and LVT</b> <b>Advance Modular Backing</b>

Special Technologies


ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests


NSF 140:	Gold Certified
Total Recycled Content	37.77%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Quarter Turn


Colorways




DEP45 Teal



DEP57 Pewter



DEP59 Black



DEP75 Bay