



Product Specifications

| | |
|----------------------------|---|
| Construction | Textured Loop |
| Backing | PremierBac® Plus (A) |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 22 oz./sy (746 grams/m2) |
| Pattern Repeat | 9.00" (w) x .71" (l) approx. (22.86cm x 1.80cm) |
| Gauge | 1/10 (3.94 rows/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Encore SD Ultima Fiber |
| Optional Warranties | Encore® 100 Fiber |


Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |


Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 68.9% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |


Colorways




FRN11 Bracken



FRN15 Salvinia



FRN51 Azolla



FRN55 Osmunda