



Product Specifications

Construction	Textile Composite
Backing	Polyester Felt Cushion
Dye Method	Solution Dyed
Wear Layer	Polyester - applied pattern
Pattern Repeat	N/A
Total Weight	4.5 oz - 5.2 oz/ square foot
Total Thickness	.205 inches
Dimensions:	18" x 36" modules
Standard Adhesive	Kinetex Adhesive
Packaging	16 modules per box (72 sq.ft)
Standard Warranties	Kinetex Adhesive

Special Technologies


Kinetex ProTex®	Standard
Kinetex Sentir®	Optional

Environmental Specifications & Tests

Carbon Footprint:	Carbon Neutral
Recyclability:	100% Closed-loop Recyclable
NSF 140:	Platinum Certified
Total Recycled Content:	45%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Herringbone, Brick, Ashlar

Colorways



IMP16 Umbra



IMP19 Taupe




IMP26 Russet



IMP38 Peat



IMP45 Marine



IMP47 Cadet



IMP48 Indigo



IMP49 Navy



IMP55 Iron



IMP56 Raven



IMP59 Ink



IMP77 Acorn