



Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus (A)
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	7200 oz./y3 (266.98 kg/m3)
Pattern Repeat	2.40" (w) x 1.80" (l) approx. (6.10cm x 4.57cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	13.2 stitches/in (5.20 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercial Premium Carpet Adhesive
Standard Warranties	<b>Encore SD Ultima Fiber</b>
Optional Warranties	<b>Endure Plus</b> <b>TitanBac Plus</b> <b>Nexus Cushion Modular Adhesive</b> <b>Encore® 100 Fiber</b>

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	68.9%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




INT12 Aspiration



INT15 Resolve



INT45 Endeavour



INT53 Steadfast



INT58 Manifest



INT77 Diligence