



Product Specifications

Construction	Patterned Scroll
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon with TeraPlex® SD PET
Face Weight	22 oz./sq yd (746 grams/m ²)
Pile Density	7333 oz./sq yd (271.91 kg/m ³)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Nylon with TeraPlex SD PET Fiber


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	42%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways




LND15 Ring




LND17 Hang UP




LND47 Operator



LND55 Area Code



LND57 Switchboard



LND75 Dial Tone



LND77 Redial