



**Installation Methods:** Parquet, Herringbone, Basketweave, Ashlar

Product Specifications

<b>Construction</b>	Tip-Sheared Scroll
<b>Backing</b>	Nexus® Modular
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	Encore® SD Ultima® (with recycled content)
<b>Face Weight</b>	22 oz./sy (746 grams/m2)
<b>Pile Density</b>	7543 oz./y3 (279.70 kg/m3)
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/12 (4.72 rows/cm)
<b>Stitches Per Inch</b>	10.5 stitches/in (4.13 stitches/cm)
<b>Standard Size</b>	12" x 48" approx. (30.48cm x 121.92cm)
<b>Standard Adhesive</b>	Commercialon Premium Modular and LVT Adhesive
<b>Standard Warranties</b>	<b>Nexus Modular</b> <b>Commercialon Adhesive for Modular Carpet &amp; LVT</b> <b>Nexus FC Cushion</b> <b>Encore SD Ultima Fiber</b>
<b>Optional Warranties</b>	<b>Commercialon High Moisture Adhesive for Modular Carpet and LVT</b> <b>Advance Modular Backing</b> <b>Encore® 100 Fiber</b>

Special Technologies

<b>ProSept® Antimicrobial</b>	Optional
<b>ProTex® Soil Release</b>	Standard
<b>Sentir® Odor-Blocker</b>	Optional

Environmental Specifications & Tests

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	46.65%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

Colorways

