



Product Specifications

Construction	Cut and Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Solution Dyed PET
Face Weight	25 oz./sy (848 grams/m2)
Pile Density	4056 oz./y3 (150.40 kg/m3)
Pattern Repeat	36.00" (w) x 38.00" (l) approx. (91.44cm x 96.52cm)
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	<b>Living Spaces</b> <b>Standard Back</b>

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



MME12 Beige




MME25 Amber



MME53 Pearl




MME55 Dappled



MME57 Walnut



MME74 Tawny



MME76 Chestnut