



Installation Methods: Herringbone, Ashlar

Product Specifications

| | |
|---------------------|---|
| Wear Layer | 20 mil |
| Thickness | 5mm |
| Finish / Coating | Enhanced UV Urethane w/ Ceramic Micro Bead |
| Pattern Repeat | Random |
| Dimensions: | 18" x 36" |
| Standard Adhesive | Commercialon Premium Modular and LVT Adhesive |
| Backing Class | Commercial Grade |
| Commercial Traffic | Heavy Commercial |
| Standard Warranties | 15 Year LVT |

Packaging

| | |
|---------------------------|-------------------------|
| Sq.ft. per piece / carton | 4.5 / 27 |
| Weight per piece / carton | 8.3 (lbs) / 49.77 (lbs) |
| Pieces per box | 6 |
| Boxes per pallet | 40 |

Special Technologies


| | |
|---------------------|-----|
| Added Antimicrobial | Yes |
|---------------------|-----|

Environmental Specifications & Tests

| | |
|--------------------|--|
| Indoor Air Quality | FloorScore® Certified |
| LEED v4 | Contributes to IAQ: Low Emitting Materials |
| End of Life | 100% Recyclable |
| Radiant Panel | Class 1 |
| ADA Compliance | Compliant For Accessible Routes |

| | |
|------------------------------------|--------|
| ASTM F2055 (Size and Tolerance) | Passes |
| ASTM F386 (Thickness) | Passes |
| ASTM F1914 (Residual Indentation) | Passes |
| ASTM F137 (Flexibility) | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resistance) | Passes |
| ASTM F1514 (Resistance to Heat) | Passes |
| ASTM F1515 (Resistance to Light) | Passes |
| ASTM E648 (Critical Radiant Flux) | Passes |
| ASTM E662 (Optical Smoke Density) | Passes |
| ASTM C1028 (Slip Resistance) | Passes |
| ASTM F970 (Static Load) | Passes |

Colorways



001 Acier



002 Terra



003 Umbra



004 Zinc



005 Earth