



Product Specifications

Construction	Cut Pile
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Solution Dyed PET
Face Weight	30 oz./sy (1017 grams/m2)
Pile Density	4462 oz./y3 (165.45 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	<b>Living Spaces</b> <b>Standard Back</b>
Optional Warranties	<b>Nexus Cushion Modular Adhesive</b>


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	0%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




PR012 Ecrú




PR025 Flax




PR053 Dawn




PR055 Stone



PR057 Umbra



PR074 Fawn



PR076 Roan