



Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	TeraPlex® SD PET with Encore® SD Nylon
Face Weight	24 oz./sy (814 grams/m2)
Pile Density	5434 oz./y3 (201.50 kg/m3)
Pattern Repeat	.20" (w) x .75" (l) approx. (.51cm x 1.91cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	8 stitches/in (3.15 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus TeraPlex® SD PET with Encore® SD Nylon


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	24.56%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways




REM15 Pebble



REM47 Aniline




REM54 Silver Grey



REM55 Cinder



REM56 Dusk



REM58 Charcoal



REM76 Coffee