

Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	TeraPlex® SD PET with Encore® SD Nylon
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	8250 oz./y3 (305.92 kg/m3)
Pattern Repeat	N/A
Gauge	1/8 (3.15 rows/cm)
Stitches Per Inch	7.33 stitches/in (2.89 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus TeraPlex® SD PET with Encore® SD Nylon

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	42%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways




RMX15 Pebble



RMX47 Aniline



RMX54 Silver Grey




RMX55 Cinder



RMX56 Dusk



RMX58 Charcoal



RMX76 Coffee