



## Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon with TeraPlex® SD PET
Face Weight	24 oz./sy (814 grams/m2)
Pile Density	5468 oz./y3 (202.76 kg/m3)
Pattern Repeat	.96" (w) x .60" (l) approx. (2.44cm x 1.52cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	8 stitches/in (3.15 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Nylon with TeraPlex SD PET Fiber

## Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


## Environmental Specifications &amp; Tests

NSF 140:	Gold Certified
Total Recycled Content	24.56%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

## Colorways




SHU15 Pebble



SHU47 Aniline



SHU54 Silver Grey



SHU55 Cinder



SHU56 Dusk



SHU58 Charcoal



SHU76 Coffee