




Installation Methods: Parquet, Herringbone, Basketweave, Ashlar

Colorways



00001 Whitewash



00002 Limestone

Product Specifications

|                     |   |
|---------------------|---|
| Wear Layer          | 20 mil  |
| Thickness           | 2.5mm   |
| Finish / Coating    | UV Cured Urethane                             |
| Pattern Repeat      | Random Stone                                  |
| Dimensions:         | 18" x 36"                                     |
| Standard Adhesive   | Commercialon Premium Modular and LVT Adhesive |
| Backing Class       | Commercial Grade                              |
| Commercial Traffic  | Heavy Commercial                              |
| Standard Warranties | 15 Year LVT                                   |

Packaging

|                           |                          |
|---------------------------|--------------------------|
| Sq.ft. per piece / carton | 4.5 / 54                 |
| Weight per piece / carton | 4.11 (lbs) / 49.36 (lbs) |
| Pieces per box            | 12                       |
| Boxes per pallet          | 40                       |

Special Technologies

|                     |     |
|---------------------|-----|
| Added Antimicrobial | Yes |
|---------------------|-----|

Environmental Specifications & Tests

|                    |  |
|--------------------|--|
| Indoor Air Quality | FloorScore® Certified                                  |
| LEED v4            | Contributes to IAQ: Low Emitting Materials             |
| End of Life        | 100% Recyclable  |
| Class / ASTM F1700 | Class III Printed Film Vinyl Plank - Type B (embossed) |
| Radiant Panel      | Class 1  |
| ADA Compliance     | Compliant For Accessible Routes                        |

|                                    |        |
|------------------------------------|--------|
| ASTM F2055 (Size and Tolerance)    | Passes |
| ASTM F386 (Thickness)              | Passes |
| ASTM F1914 (Residual Indentation)  | Passes |
| ASTM F137 (Flexibility)            | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resistance)    | Passes |
| ASTM F1514 (Resistance to Heat)    | Passes |
| ASTM F1515 (Resistance to Light)   | Passes |
| ASTM E648 (Critical Radiant Flux)  | Passes |
| ASTM E662 (Optical Smoke Density)  | Passes |
| ASTM C1028 (Slip Resistance)       | Passes |
| ASTM F970 (Static Load)            | Passes |