



Installation Methods: Parquet, Herringbone, Basketweave, Ashlar

Product Specifications

Wear Layer	20mil
Thickness	5mm
Finish / Coating	UV Cured Urethane
Pattern Repeat	Random Stone
Dimensions:	18" x 36"
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Optional Warranties	Nexus Cushion Modular Adhesive

Packaging

Sq.ft. per piece / carton	4.5 / 27
Weight per piece / carton	8.3 (lbs) / 49.77 (lbs)
Pieces per box	6
Boxes per pallet	40

Special Technologies

Added Antimicrobial	Yes
---------------------	-----


Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified
LEED v4	Contributes to IAQ: Low Emitting Materials
End of Life	100% Recyclable
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)
Radiant Panel	Class 1
ADA Compliance	Compliant For Accessible Routes
ASTM F2055 (Size and Tolerance)	Passes
ASTM F386 (Thickness)	Passes
ASTM F1914 (Residual Indentation)	Passes
ASTM F137 (Flexibility)	Passes
ASTM F2199 (Dimensional Stability)	Passes
ASTM F925 (Chemical Resistance)	Passes
ASTM F1514 (Resistance to Heat)	Passes
ASTM F1515 (Resistance to Light)	Passes
ASTM E648 (Critical Radiant Flux)	Passes
ASTM E662 (Optical Smoke Density)	Passes
ASTM C1028 (Slip Resistance)	Passes
ASTM F970 (Static Load)	Passes

Colorways



001 Whitewash



002 Limestone