



Product Specifications

Construction	Tip-Sheared Scroll
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	24 oz./sy (814 grams/m2)
Pile Density	9391 oz./y3 (348.22 kg/m3)
Pattern Repeat	24.00" (w) x 47.30" (l) approx. (60.96cm x 120.14cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	11.66 stitches/in (4.59 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	50%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




STT10 Tatami



STT32 Tinsel




STT45 Shadow



STT47 Barkcloth



STT48 Denim



STT52 Grey Twill



STT55 Stonewash



STT58 Rattan



STT72 Knitting Nee...



STT76 Corduroy



STT77 Tapestry Ta...



STT86 Shuttle Bro...