



Product Specifications

Construction	Textured Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	20 oz./sy (678 grams/m2)
Pile Density	5169 oz./y3 (191.67 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	11.33 stitches/in (4.46 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Nexus Cushion Modular Adhesive Encore® 100 Fiber

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	25%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

 SRD13 Sand	 SRD14 Glacier	 SRD45 Seascape	 SRD46 Cadet	 SRD53 Dockside	 SRD54 Pepper
 SRD56 Dorsal	 SRD58 Cauldron	 SRD59 Carbon	 SRD73 Toast	 SRD76 Truffle	 SRD77 Pinecone