



Product Specifications

Construction	Textured Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	5318 oz./y3 (197.19 kg/m3)
Pattern Repeat	N/A
Stitches Per Inch	12.66 stitches/in (4.98 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	25%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



SRD13 Sand



SRD14 Glacier



SRD45 Seascape



SRD46 Cadet



SRD53 Dockside




SRD54 Pepper



SRD56 Dorsal



SRD58 Cauldron




SRD59 Carbon



SRD73 Toast



SRD76 Truffle



SRD77 Pinecone