



Installation Methods: Herringbone, Basketweave, Ashlar

Product Specifications

| | |
|---------------------|--|
| Construction | Patterned Scroll |
| Backing | Nexus® Modular |
| Dye Method | Solution Dyed |
| Fiber Type | TeraPlex® SD PET |
| Face Weight | 16 oz./sy (543 grams/m2) |
| Pile Density | 9143 oz./y3 (339.03 kg/m3) |
| Pattern Repeat | N/A |
| Gauge | 1/12 (4.72 rows/cm) |
| Stitches Per Inch | 10.2 stitches/in (4.02 stitches/cm) |
| Standard Size | 18" x 36" approx. (45.72cm x 91.44cm) |
| Standard Adhesive | Commercialon Premium Modular and LVT Adhesive |
| Optional Adhesive | TileTabs |
| Standard Warranties | Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Nexus FC Cushion |
| Optional Warranties | Commercialon High Moisture Adhesive for Modular Carpet and LVT Advance Modular Backing Nexus Cushion Modular Adhesive Advance Modular Adhesive Tile Tabs |


Special Technologies

| | |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |


Environmental Specifications & Tests

| | |
|------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 41.5% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |


Colorways



TME32 Solar Linen




TME48 Cosmic Blue




TME55 Pythiad Sil...



TME56 Interlapse G...



TME59 Jet Lag



TME78 Standard T...