



**Installation Methods:** Parquet, Herringbone, Basketweave, Ashlar

**Product Specifications**

<b>Construction</b>	Patterned Loop
<b>Backing</b>	Nexus® Modular
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	TeraPlex® SD PET
<b>Face Weight</b>	19 oz./sq (644 grams/m2)
<b>Pile Density</b>	6706 oz./y3 (248.66 kg/m3)
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/12 (4.72 rows/cm)
<b>Standard Size</b>	18" x 36" approx. (45.72cm x 91.44cm)
<b>Standard Adhesive</b>	Commercialon Premium Modular and LVT Adhesive
<b>Optional Adhesive</b>	TileTabs
<b>Standard Warranties</b>	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Nexus FC Cushion
<b>Optional Warranties</b>	Commercialon High Moisture Adhesive for Modular Carpet and LVT Advance Modular Backing Nexus Cushion Modular Adhesive Tile Tabs











**Special Technologies**

<b>ProSept® Antimicrobial</b>	Optional
<b>ProTex® Soil Release</b>	Standard
<b>Sentir® Odor-Blocker</b>	Optional

**Environmental Specifications & Tests**

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	40.1%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

**Colorways**

					
TRY10 Commutable	TRY12 Capable	TRY15 Similar	TRY16 Replaceable	TRY33 Exchange	TRY40 Switchable
					
TRY43 Alteration	TRY46 Additionally	TRY56 Function	TRY58 Standardized		