



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

Construction	Patterned Scroll
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	6712 oz./y3 (248.89 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Optional Adhesive	TileTabs
Standard Warranties	<b>Nexus Modular</b> <b>Commercialon Adhesive for Modular Carpet &amp; LVT</b> <b>Nexus FC Cushion</b> <b>Encore SD Ultima Fiber</b>
Optional Warranties	<b>Commercialon High Moisture Adhesive for Modular Carpet and LVT</b> <b>Tile Tabs</b> <b>Encore® 100 Fiber</b>

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	46.65%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



TEM12 Lightheart...



TEM15 Pulse




TEM18 Swing



TEM22 Snappy




TEM44 Animated




TEM47 Bluestreak



TEM52 Sparkling



TEM55 Double Time



TEM58 Cadence



TEM84 Screamin