



Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	9290 oz./y3 (344.48 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Nexus FC Cushion Encore SD Ultima Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT Advance Modular Backing Tile Tabs Encore® 100 Fiber

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	46.65%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Colorways

WTC11 Bone White	WTC15 Gamboge	WTC33 Sap Green	WTC35 Celadon	WTC37 Turquoise	WTC38 Phthalo Gr...
WTC44 Cerulean	WTC46 Lapiz	WTC47 Ultramarine	WTC49 Dark Cobalt	WTC51 Smoke	WTC54 Payne's Gr...
WTC56 Lead Gray	WTC59 Soot Black	WTC68 Rose Madd...	WTC76 Raw Sienna	WTC78 Umber	WTC86 Vermillion
WTC88 Scarlet Red	WTC98 Mars Violet				