



Product Specifications

|                     |   |
|---------------------|---|
| Construction        | Textured Loop   |
| Backing             | Nexus® Modular  |
| Dye Method          | Solution Dyed   |
| Fiber Type          | Encore® SD Ultima® (with recycled content)  |
| Face Weight         | 22 oz./sy (746 grams/m2)  |
| Pile Density        | 9290 oz./y3 (344.48 kg/m3)  |
| Pattern Repeat      | N/A   |
| Gauge               | 1/10 (3.94 rows/cm)   |
| Standard Size       | 18" x 36" approx. (45.72cm x 91.44cm)   |
| Standard Adhesive   | Commercialon Premium Modular and LVT Adhesive   |
| Optional Adhesive   | TileTabs  |
| Standard Warranties | Nexus Modular<br>Commercialon Adhesive for Modular Carpet & LVT<br>Nexus FC Cushion<br>Encore SD Ultima Fiber               |
| Optional Warranties | Commercialon High Moisture Adhesive for Modular Carpet and LVT<br>Advance Modular Backing<br>Tile Tabs<br>Encore® 100 Fiber |

Special Technologies

Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 46.65%                             |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |

Installation Methods: Parquet, Herringbone, Basketweave, Brick, Ashlar

Colorways

