



Product Specifications

|                     |   |
|---------------------|---|
| Wear Layer          | 20 mil  |
| Thickness           | 2.5mm   |
| Finish / Coating    | Enhanced UV Urethane w/ Ceramic Micro Bead    |
| Pattern Repeat      | Random Wood                                   |
| Edge Treatment      | Micro-Bevel                                   |
| Dimensions:         | 7" x 48"                                      |
| Standard Adhesive   | Commercialon Premium Modular and LVT Adhesive |
| Backing Class       | Commercial Grade                              |
| Commercial Traffic  | Heavy Commercial                              |
| Standard Warranties | 10 Year LVT                                   |

Packaging

|                           |                          |
|---------------------------|--------------------------|
| Sq.ft. per piece / carton | 2.33 / 42                |
| Weight per piece / carton | 1.96 (lbs) / 35.28 (lbs) |
| Pieces per box            | 18                       |
| Boxes per pallet          | 50                       |

Special Technologies

|                     |     |
|---------------------|-----|
| Added Antimicrobial | Yes |
|---------------------|-----|

Environmental Specifications & Tests

|                                    |  |
|------------------------------------|--|
| Indoor Air Quality                 | FloorScore® Certified                                  |
| LEED v4                            | Contributes to IAQ: Low Emitting Materials             |
| End of Life                        | 100% Recyclable  |
| Class / ASTM F1700                 | Class III Printed Film Vinyl Plank - Type B (embossed) |
| Radiant Panel                      | Class 1  |
| ADA Compliance                     | Compliant For Accessible Routes                        |
| ASTM F2055 (Size and Tolerance)    | Passes   |
| ASTM F386 (Thickness)              | Passes   |
| ASTM F1914 (Residual Indentation)  | Passes   |
| ASTM F137 (Flexibility)            | Passes   |
| ASTM F2199 (Dimensional Stability) | Passes   |
| ASTM F925 (Chemical Resistance)    | Passes   |
| ASTM F1514 (Resistance to Heat)    | Passes   |
| ASTM F1515 (Resistance to Light)   | Passes   |
| ASTM E648 (Critical Radiant Flux)  | Passes   |
| ASTM E662 (Optical Smoke Density)  | Passes   |
| ASTM C1028 (Slip Resistance)       | Passes   |
| ASTM F970 (Static Load)            | Passes   |

Colorways



001 Ironwood



002 Sequoia



007 Danish Teak



008 Acacia



009 Silver Ash



010 Mocha



011 Tawny Ash



012 Hazel



013 Tamarack



014 Honey Maple



[www.efcontractflooring.com](http://www.efcontractflooring.com)