



Dart
kinetex





Dart

A classic palette, with a dash of highly saturated bravado thrown into the mix. Optimize any space, add accents and more with this highly usable tile — with all of the performance attributes that Kinetex® offers to the floor.




COORDINATING PALETTE


Beyond the beauty of individual products, EF Contract's flooring **coordinates effortlessly** across all of our product platforms - modular carpet tile, broadloom, LVT and Kinetex textile composite flooring. This offering enables you to blend a range of designs to create **palettes** that meet the demands of each unique space.

1	DOUBLE - FLASH	DLE34	KINETEX
2	WOODLANDS II - IRONWOOD	001	LVT
3	CHINOOK - WHIRLWIND	CNK001	KINETEX
4	DART - STREAK	DAR99	KINETEX
5	CONTROL II - VIOLET	CNL96	MODULAR
6	DISTRICT II - DAMSON	DIS97	MODULAR
7	INTRIGUE - TEMPT	ITR95	KINETEX
8	WATERCOLORS - MARS VIOLET	WTC98	MODULAR
9	CASCADE - CATARACT	CSC99	KINETEX
10	PLAYBOOK - SHADOW	010	LVT


DART 24" x 24" MODULAR | 12" x 48" PLANK




DAR76
GALLOP




DAR74
BOLT




DAR44
WHIZ



DAR25
DASH




DAR79
ZIP



DAR45
SPRINT



DAR34
FLASH



DAR24
SURGE



DAR59
ZOOM



DAR49
HURRY



DAR99
STREAK



DAR87
SPRING



DAR77
FLY

*THESE COLORS SHOULD BE USED AS BORDERS & ACCENTS ONLY

SCAN ME!




Scan to order
samples or
check inventory.



1. DURABILITY

Kinetex delivers enduring performance, year after year. One of the most thoroughly tested flooring products on the market, it has outstanding dimensional stability and unparalleled crush resistance.




Kinetex has withstood more than 5 million foot traffic events.

2. MAINTENANCE

Tough to wear out, easy to maintain. With vacuuming and encapsulation cleaning, Kinetex looks like new, year after year. Thanks to a lightweight face construction, Kinetex retains less water than carpet and dries faster. It is easily sanitized and resists the most challenging staining agents.

Life Cycle Costs:
INSTALLATION AND MAINTENANCE



3. MOISTURE TOLERANCE

The most common subfloor, concrete, can release excessive moisture and destroy floor covering systems—unless costly precautions are taken before installation. But moisture mitigation isn't necessary with Kinetex; its breathable nature allows moisture to pass through its backing, instead of trapping it underneath. Kinetex textile composite flooring will perform in elevated RH slabs up to 100%.

NO VAPOR BARRIER REQUIRED—
regardless if the slab is new or old, regardless of hydrostatic pressure

100% RH TOLERANCE


BREATHABLE
No trapped moisture. 3rd party tested and verified.

Thousands of installations worldwide since 2012. NO MOISTURE-RELATED CLAIMS.

4. HEALTH

Kinetex minimizes air particulates that trigger allergies and cause infection. It easily surpasses California's 01350 requirements—the most popular U.S. standard for evaluating and restricting VOC emissions indoors.

Easy Breathing




(ESO Fine Test Dust 12103-142) Foot Traffic Dust Emissions Test

5. SAFETY

Kinetex is the only wall-to-wall textile floor covering certified as High-Traction by the National Floor Safety Institute. Its innovative construction creates one of the most slip-resistant flooring surfaces ever tested—wet or dry—to prevent falls before they happen.


Gaining Traction



6. ACOUSTICS

Kinetex delivers unparalleled acoustic performance, with one of the highest Noise Reduction Coefficients (NRC) and Impact Insulation Classifications (IIC) ratings of any commercial flooring product.


Keeping Quiet



7. COMFORT

Kinetex, a soft textile surface with a high-density backing, has exceptional anti-fatigue properties and minimal rolling resistance. Because it can absorb energy, Kinetex has the potential to reduce repetitive foot stress injuries and other injuries related to standing and frequent movement from place to place.


Step-by-Step Support



8. SUSTAINABILITY

Made with 45% post-consumer recycled content, each Kinetex tile contains the equivalent of 27 used water bottles. This dematerialized flooring product and its longer life mean that Kinetex has a much smaller environmental footprint than other commercial flooring options. Kinetex is NSF/ANSI-140 Platinum certified (the industry-leading standard for sustainability) and has a Red List Free DECLARE label. Furthermore, Kinetex has been verified as a Carbon Neutral product

Second Chances



Each Kinetex tile contains the equivalent of 27 plastic water bottles.

KINETEX INSTALLATION

Installing Kinetex is as easy as traditional modular carpet, however special attention should be applied until installers gain experience with module placement. Installers should perform site and material conditioning, surface preparation, and concrete pH and moisture testing as if they were installing EF Contract carpet modules. Because it is such a lightweight material the modules cut very easily, reducing installation time. Kinetex uses EF Contract's proven adhesive systems with lifetime performance warranties.

Kinetex Adhesive

Kinetex Adhesive is formulated for Kinetex textile composite flooring products and is built to bond the textile composite to the properly prepared substrates for the life of the installation. Products with Kinetex Adhesive will perform in elevated RH slabs up to 100%.

Please see the Kinetex installation instructions for full installation details.

PRODUCT DETAILS

WARRANTIES

We stand behind every aspect of Kinetex and extend certain lifetime warranties. Each warranty is covered for the useful life of the product, provided that installation and maintenance is in accordance with EF Contract's Kinetex Installation instructions.

Wear Layer Warranties

Product Performance	Colorfastness to Light & Crocking	Stain Removal	Static Protection
Lifetime	Lifetime	Lifetime	Lifetime

Backing Warranties

Protection from Edge Ravel	Protection from Delamination Failure	Dimensional Stability
Lifetime	Lifetime	Lifetime



©2023 EF Contract, LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law. Due to the unique visual characteristics of modular carpets, pattern repeats and pattern run-off seams may appear more noticeable than in broadloom carpets. Such visual characteristics do not constitute a manufacturing defect, and as such, should be considered when selecting modular carpet and its installation.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer's, and not EF Contract's responsibility.

*NRC rating is a measure of the effectiveness of a material in absorbing sound. The higher the NRC rating, the greater the ability of the flooring product to absorb airborne noise. Independent laboratory testing of Kinetex has shown an average NRC rating of 0.30 (bare concrete flooring will typically provide a NRC Rating of 0.015).

**IIC is a rating of the insulation from impact noise. The higher the IIC rating, the greater the sound insulation. Independent laboratory testing of Kinetex has shown an average IIC Rating of .64 (bare concrete flooring will typically provide an IIC Rating of 34) NOTE: Test results and testing laboratory will vary, and the above information is not guaranteed.

PRODUCT DETAILS

STYLE	DART KDAR
WEAR LAYER	SOLUTION DYED POLYESTER
BACKING	POLYESTER FELT CUSHION
TOTAL WEIGHT (NOMINAL AVERAGE)	4.5 OZ - 5.2 OZ / SQUARE FOOT
TOTAL THICKNESS (NOMINAL AVERAGE)	0.205 IN
DIMENSIONS	24" W X 24" L MODULES 12" W X 48" L PLANK
PACKAGING	18 MODULES PER BOX, 72 SQUARE FEET
RECYCLED CONTENT	>55% POST-CONSUMER/INDUSTRIAL
LEED SCORECARD	IEQ 4.1 AND IEQ 4.3
NSF/ANSI 140 CERTIFICATION	PLATINUM
FLOORING RADIANT PANEL	CLASS 1
SMOKE DENSITY	LESS THAN 450 (FLAMING & NON-FLAMING)
ELECTROSTATIC PROPENSITY	LESS THAN 3.0 KV
COLORFASTNESS TO LIGHT	RATING OF 4.0 OR GREATER
COLORFASTNESS TO CROCKING	RATING OF 4.0 OR GREATER
WATER REPELLENCY	RATING OF 4.0 OR GREATER
APPEARANCE RETENTION	4.5 OR GREATER
SLIP RESISTANCE	COMPLIES WITH ADA GUIDELINES FOR LEVEL SURFACE NFSI CERTIFIED HIGH-TRACTION
THERMAL INSULATION	R-4
NOISE REDUCTION COEFFICIENT	NRC RATING: 0.30*
IMPACT INSULATION CLASSIFICATION	IIC RATING: 64**
STAIN RESISTANCE	RESISTS MOST CHALLENGING STAINS
BLEACH RESISTANCE	RATING OF 4.0 OR GREATER (5% CHLORINE BLEACH /95% WATER)
INDOOR AIR QUALITY CERTIFICATION	CRI GREEN LABEL PLUS™
ADHESIVES	KINETEX ADHESIVE (FULL-SPREAD PRESSURE-SENSITIVE)

RECOMMENDED INSTALLATION METHODS

				12" W X 48" L PLANK*
QUARTER TURN	BRICK	ASHLAR	STAIR STEP	*PLANKS FOR THIS KINETEX STYLE ARE NOT INTENDED FOR INSTALLATION AS A FIELD PRODUCT AND ARE LIMITED TO BORDERS AND ACCENTS ONLY.



PO Box 2207
Dalton, Georgia 30722
U.S.A.

800.451.1250
efcontract.com