

Imprint

kinetex





Imprint

The repetition of impression captures our attention with soft, rhythmic patterns of singular beauty. Inspired by the delicate mark pressed from a piece of cloth, Imprint delivers calm elegance and refined luxury to any space.





18" X 36" MODULAR

IMPRINT



IMP55 | IRON



IMP45 | MARINE



IMP47 | CADET



IMP49 | NAVY



IMP56 | RAVEN



IMP19 | TAUPE



IMP16 | UMBRA



IMP38 | PEAT



IMP59 | INK


SCAN ME!



Scan to order samples or check inventory.

1. DURABILITY

Kinetex delivers enduring performance, year after year. One of the most thoroughly tested flooring products on the market, it has outstanding dimensional stability and unparalleled crush resistance.




Kinetex has withstood more than 5 million foot traffic events.

2. MAINTENANCE

Tough to wear out, easy to maintain. With vacuuming and encapsulation cleaning, Kinetex looks like new, year after year. Thanks to a lightweight face construction, Kinetex retains less water than carpet and dries faster. It is easily sanitized and resists the most challenging staining agents.

Life Cycle Costs:
INSTALLATION AND MAINTENANCE



3. MOISTURE TOLERANCE

The most common subfloor, concrete, can release excessive moisture and destroy floor covering systems—unless costly precautions are taken before installation. But moisture mitigation isn't necessary with Kinetex; its breathable nature allows moisture to pass through its backing, instead of trapping it underneath. Kinetex textile composite flooring will perform in elevated RH slabs up to 100%.

NO VAPOR BARRIER REQUIRED—
regardless if the slab is new or old, regardless of hydrostatic pressure

100% RH TOLERANCE


BREATHABLE
No trapped moisture. 3rd party tested and verified.

Thousands of installations worldwide since 2012. NO MOISTURE-RELATED CLAIMS.

4. HEALTH

Kinetex minimizes air particulates that trigger allergies and cause infection. It easily surpasses California's 01350 requirements—the most popular U.S. standard for evaluating and restricting VOC emissions indoors.

Easy Breathing




(ESO Fine Test Dust 12103-142) Foot Traffic Dust Emissions Test

5. SAFETY

Kinetex is the only wall-to-wall textile floor covering certified as High-Traction by the National Floor Safety Institute. Its innovative construction creates one of the most slip-resistant flooring surfaces ever tested—wet or dry—to prevent falls before they happen.

Gaining Traction




*wet soapy surfaces



6. ACOUSTICS

Kinetex delivers unparalleled acoustic performance, with one of the highest Noise Reduction Coefficients (NRC) and Impact Insulation Classifications (IIC) ratings of any commercial flooring product.


Keeping Quiet



7. COMFORT

Kinetex, a soft textile surface with a high-density backing, has exceptional anti-fatigue properties and minimal rolling resistance. Because it can absorb energy, Kinetex has the potential to reduce repetitive foot stress injuries and other injuries related to standing and frequent movement from place to place.

Step-by-Step Support



Source: Conducted by an Independent Laboratory

8. SUSTAINABILITY

Made with 45% post-consumer recycled content, each Kinetex tile contains the equivalent of 27 used water bottles. This dematerialized flooring product and its longer life mean that Kinetex has a much smaller environmental footprint than other commercial flooring options. Kinetex is NSF/ANSI-140 Platinum certified (the industry-leading standard for sustainability) and has a Red List Free DECLARE label. Furthermore, Kinetex has been verified as a Carbon Neutral product.

Second Chances

45% post-consumer content



Each Kinetex tile contains the equivalent of 27 plastic water bottles.

KINETEX INSTALLATION

Although Kinetex is a modular tile, it does not install like traditional modular carpet. Installers should carefully read the full Kinetex installation instructions. Special attention should be applied until installers gain experience with module placement. Installers should perform site and material conditioning and surface preparation, and there should be no condensation or standing water at the time of installation. Kinetex material is lightweight and is easy to cut, which reduces installation time. Kinetex uses EF Contract's proven adhesive system with a lifetime performance warranty.

Kinetex Adhesive

Kinetex Adhesive is formulated for Kinetex textile composite flooring products and is built to bond the textile composite to the properly prepared substrates for the life of the installation. Products with Kinetex Adhesive will perform in elevated RH slabs up to 100%.

Please see the Kinetex installation instructions for full installation details.

PRODUCT DETAILS

TECHNOLOGIES

High-Def Color Technology™

EF Contract achieves next-generation innovation with the development of High-Def Color Technology. This latest engineering capability provides Kinetex products with crisp color, vibrant patterns and dimensional design that rivals that of soft surface flooring.



WARRANTIES

We stand behind every aspect of Kinetex and extend certain lifetime warranties. Each warranty is covered for the useful life of the product, provided that installation and maintenance is in accordance with EF Contract's Kinetex Installation instructions.

Wear Layer Warranties

Product Performance	Colorfastness to Light & Crocking	Stain Removal	Static Protection
Lifetime	Lifetime	Lifetime	Lifetime

Backing Warranties

Protection from Edge Ravel	Protection from Delamination Failure	Dimensional Stability
Lifetime	Lifetime	Lifetime



2024 EF Contract, LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law. Due to the unique visual characteristics of modular carpets, pattern repeats and pattern run-off seams may appear more noticeable than in broadloom carpets. Such visual characteristics do not constitute a manufacturing defect, and as such, should be considered when selecting modular carpet and its installation.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer's, and not J+J Flooring's responsibility.


*NRC rating is a measure of the effectiveness of a material in absorbing sound. The higher the NRC rating, the greater the ability of the flooring product to absorb airborne noise. Independent laboratory testing of Kinetex has shown an average NRC rating of 0.30 (bare concrete flooring will typically provide a NRC Rating of 0.015).

**IIC is a rating of the insulation from impact noise. The higher the IIC rating, the greater the sound insulation. Independent laboratory testing of Kinetex has shown an average IIC Rating of .64 (bare concrete flooring will typically provide an IIC Rating of 34) NOTE: Test results and testing laboratory will vary, and the above information is not guaranteed.

PRODUCT DETAILS

STYLE	IMPRINT KIMP
WEAR LAYER	SOLUTION DYED POLYESTER - APPLIED PATTERN (PRODUCED WITH HIGH-DEF COLOR TECHNOLOGY™)
BACKING	POLYESTER FELT CUSHION
TOTAL WEIGHT (NOMINAL AVERAGE)	4.5 OZ – 5.2 OZ / SQUARE FOOT
TOTAL THICKNESS (NOMINAL AVERAGE)	0.205 IN
DIMENSIONS	18" W X 36" L
PACKAGING	16 MODULES PER BOX, 72 SQUARE FEET
CARBON FOOTPRINT	CARBON NEUTRAL
RED LIST FREE	DECLARE LABEL
RECYCLED CONTENT	>55% (POST CONSUMER/INDUSTRIAL)
LEED SCORECARD	IEQ 4.1 AND IEQ 4.3
NSF/ANSI 140 CERTIFICATION	PLATINUM
FLOORING RADIANT PANEL	CLASS 1
SMOKE DENSITY	LESS THAN 450 (FLAMING & NON-FLAMING)
ELECTROSTATIC PROPENSITY	LESS THAN 3.0 KV
COLORFASTNESS TO LIGHT	RATING OF 4.0 OR GREATER
COLORFASTNESS TO CROCKING	RATING OF 4.0 OR GREATER
WATER REPELLENCY	RATING OF 4.0 OR GREATER
APPEARANCE RETENTION	4.0 OR GREATER
SLIP RESISTANCE	COMPLIES WITH ADA GUIDELINES FOR LEVEL SURFACE NFSI CERTIFIED HIGH-TRACTION
THERMAL INSULATION	R-4
NOISE REDUCTION COEFFICIENT	NRC RATING: 0.30*
IMPACT INSULATION CLASSIFICATION	IIC RATING: 64**
STAIN RESISTANCE	RESISTS MOST CHALLENGING STAINS
INDOOR AIR QUALITY CERTIFICATION	CRI GREEN LABEL PLUS™
ADHESIVE	KINETEX ADHESIVE (FULL-SPREAD PRESSURE-SENSITIVE)

RECOMMENDED INSTALLATION METHODS





PO Box 2207
Dalton, Georgia 30722
U.S.A.

800.451.1250
efcontract.com
AX8023M08